

# ETS 64-R



## ETS 64-R

- Electric motor swing door drive EN 3-6, for doors up to 250 kg, with FS/RS requirement.
- Tested in accordance with DIN 18263-4, approved by the DIBt / design certification
- Height 95 mm, width 690 mm, depth 120 mm. Weight 10.5 kg
- Ambient temperature -15 to +50°, max. relative humidity 85%, IP 40 (42)
- Mains power: 230 VAC, 50 Hz, 10/13 A, power consumption max. 560 W.
- Output power: 24 VDC, max. 2.0 A
- Lintel depth max. 250 mm (SGS), 50 mm (GS)
- Door opening angle max. 105°
- Hold-open time 0...60 s / 0...180 s.
- Motor damping continuously adjustable without power (potentiometer)
- Additional functions: Servo support, Push & Go, Low Energy, wind load compensation
- Design: Cover hood stainless steel matt brushed

<b>ETS 64-R (ER)</b>	5030014716	Swing door drive for doors up to 250 kg with FS/RS approval <ul style="list-style-type: none"><li>▪ For slide rail pulling (max. EN 5) or arm pushing (max. EN 6)</li></ul>
<b>ETS 64-R GDS (ER)</b>	5030014717	Swing door drive for doors up to 250 kg with FS/RS approval <ul style="list-style-type: none"><li>▪ For slide rail pushing (max. EN 6)</li></ul>
<b>ETS 64-R-IRM (ER)</b>	5030034212	Swing door drive with integrated smoke switch <ul style="list-style-type: none"><li>▪ For doors up to 250 kg with FS/RS approval</li><li>▪ For slide rail pulling (max. EN 5) or arm pushing (max. EN 6)</li></ul>
<b>ETS 64-R-IRM GSD (ER)</b>	5030034214	Swing door drive with integrated smoke switch <ul style="list-style-type: none"><li>▪ For doors up to 250 kg with FS/RS approval</li><li>▪ For slide rail pushing (max. EN 6)</li></ul>

---

## ETS 64-R SETS ■ Single-leaf

---

<b>Set ETS 64-IRM-SGS-AV-30-Flat-HAT</b>	5030057207	Single-leaf swing door drive set FS/RS (EN 6) with arm Push (opposite hinge side), comprising: <ul style="list-style-type: none"><li>▪ 1 x ETS 64-R-IRM (ER)</li><li>▪ 1 x MPL set 64</li><li>▪ 1 x SGS ETS 250-ER</li><li>▪ 1 x AV 30-ER</li></ul>
<b>Set ETS 64-IRM-GSD-AV-30-Flat-HAT</b>	5030058461	Single-leaf swing door drive set FS/RS (EN 6) with slide rail Push (opposite hinge side), comprising: <ul style="list-style-type: none"><li>▪ 1 x ETS 64-R-IRM (ER)</li><li>▪ 1 x MPL set 64</li><li>▪ 1 x GS-620-ÖB-ER</li><li>▪ 1 x AV 30-ER</li></ul>
<b>Set ETS-64-IRM-GSZ-AV-30-Flat-HAT</b>	5030057208	Single-leaf swing door drive set FS/RS (EN 5) with slide rail Pull (hinge side): <ul style="list-style-type: none"><li>▪ 1 x ETS-64-IRM-ER</li><li>▪ 1 x MPL set 64</li><li>▪ 1 x GS-620-ÖB-ER</li><li>▪ 1 x AV-30-ER</li></ul>

---

All sets include: 1 x FlatScan set, black, 1 x HAT 02, 1 x test book + inspection label

---

## ETS 64-R SETS ■ Double-leaf

---

<b>Set ETS-64-IRM-2-SGS-SRI-AV-30-Flat-HAT</b>	5030057210	Double-leaf swing door drive set FS/RS (EN 6), comprising: <ul style="list-style-type: none"><li>▪ 1 x ETS 64-R (ER) active leaf</li><li>▪ 1 x ETS 64-R-IRM (ER) passive leaf</li><li>▪ 2 x MPL set 64</li><li>▪ 2 x SGS ETS 250-ER</li></ul>
<b>Set ETS-64-IRM-2-GSZ-SRI-AV-30-Flat-HAT</b>	On request	Double-leaf swing door drive set FS/RS (EN 6), comprising: <ul style="list-style-type: none"><li>▪ 1 x ETS 64-R (ER) active leaf</li><li>▪ 1 x ETS 64-R-IRM (ER) passive leaf</li><li>▪ 2 x MPL set 64</li><li>▪ 2 x GS-620-ÖB-ER</li></ul>
<b>Set ETS-64-IRM-2-GSD-SRI-AV-30-Flat-HAT</b>	On request	Double-leaf swing door drive set FS/RS (EN 6), comprising: <ul style="list-style-type: none"><li>▪ 1 x ETS 64-R-GSD-ER active leaf</li><li>▪ 1 x ETS 64-IRM-GSD-ER passive leaf</li><li>▪ 2 x GS-620-ÖB-ER</li><li>▪ 2 x MPL set 64</li><li>▪ 2 x SGS ETS 250-ER</li></ul>

---

All sets include:

- 1 x SRI
  - 1 x CAN
  - 2 x AV-30-ER
  - 2 x FlatScan sets, black
  - 1 x V-ETS 73/64-ER
  - 1 x HAT 02
  - 1 x test book + inspection label
-

**ECO Schulte GmbH & Co. KG**

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

[info@eco-schulte.de](mailto:info@eco-schulte.de)

[www.eco-schulte.de](http://www.eco-schulte.de)

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

## ■ SYSTEM TECHNOLOGY FOR THE DOOR

