


BUS AND STAND-ALONE

EMERGENCY BUTTON

- Emergency button, backlit in red with two force-guided
- contacts (normally open/normally closed), capacity 30 VDC, 1.2 A
- 4 inputs with status displays in red, green, yellow
- Integrated buzzer (negative-edge-triggered)
- Contact capacity: Emergency button 1.2 A/sabotage contact 30 V, 50
- Plug-in terminals with screw connections
- Operating voltage: 12 24 VDC, ±10%, max. 200 mA
- Dimensions (L x W): 88 x 88 mm (Size: 1 x 1)
- Included separately in package: Info label for emergency button
- Luminescent, arrow pointing down



Product	Article number	Product code	Description
Emergency button with 2x normally closed con- tacts, green	5030036656	NT12-100	Operating voltage 12 - 24 V max. 200 mA 88 x 88 mm
Emergency button with 2x closers, white	5030036657	NT11-100	Operating voltage 12 - 24 V max. 200 mA 88 x 88 mm
Emergency button With 1x normally closed contact, 1x normally open contact, green	5030036658	NT12-1OS	Operating voltage 12 - 24 V max. 200 mA 88 x 88 mm
Emergency button with 1x normally closed contact, 1x normally open contact, white	5030036659	NT11-1OS	Operating voltage 12 - 24 V max. 200 mA 88 x 88 mm
Emergency button with 2x normally closed contacts, option with relay green	5030036660	NTR12-100	Operating voltage 12 - 24 V max. 200 mA 88 x 88 mm

Accessories	Article number	Product code	Description	
Emergency button – On-wall frame				
On-wall housing 88 x 88 x 48 mm in the colour green	5030036734	APR1-G55	Must be recorded separately for on-wall systems.	
On-wall housing, 88 x 88 x 48 mm in the colour white	5030036729	APR1-W55	Must be recorded separately for on-wall systems.	
Emergency button – In-wall box				
In-wall box 68 x 68 x	5030036737	A1004	Must be recorded separately for in-wall inquiries.	

52 mm in the colour grey



ECO Schulte GmbH & Co. KG

Telephone +49 2373 9276 - 0 Telefax +49 2373 9276 - 40

info@eco-schulte.de www.eco-schulte.de

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured individually for customers and sometimes require longer delivery times and minimum purchase quantities. Our Customer Service Center will be happy to advise you on this.

■ SYSTEM TECHNOLOGY FOR THE DOOR



