## Declaration of performance No. DOP-1935-BK14-00099-17



1. Unique code for the product type:

#### ECO Objektbänder Ø 20, Rollenlänge 160 mm Series OBX-20-xxx/160, Series OBN-20-xxx/160

2. Purpose of application or purposes of application intended by the manufacturer of the construction product in accordance with the applicable harmonised technical specification:

### To guide and/or bear single- and double-leaf hinged doors for fire / smoke resistance closures

3. Name, registered brand name or registered brand and contact address of the manufacturer in accordance with Article 11, Paragraph 5:

#### ECO Schulte GmbH & Co. KG Iserlohner Landstraße 89 D-58706 Menden

4. If appropriate, name and contact address of the authorised representative who is assigned to the tasks in accordance with Article 12, Paragraph 2:

N/A

5. Harmonised standard:

EN 1935:2002/AC:2003

6. Notified body:

The notified certification body for in-house production checks **no. 0432** has carried out the initial inspection of the manufacturing plant and factory production checks as well as the continuous monitoring, assessment and evaluation of the factory production checks and has issued the certificate of conformity of factory production checks **(to 0432-CPR-00099-17).** 

Notified product certification body no. 0432

# Declaration of performance No. DOP-1935-BK14-00099-17



#### 7. Declared performance:

Essential characteristics		Performance	Harmonised technical specification
Self-c	losing		
5.1	Initial friction torque measurements	Class 14: Passed	
5.2.1	Load-deformation	Class 14: 320.0 kg	
5.2.2	Overload	Class 14: 480.0 kg	
5.3	Shear strength	Class 14: 15.0 kN	
5.6	Hinges for use on fire/ smoke resistance doors	Class 1: For use on fire-/ smoke resistance doors acc. to a test of EN 1634-1	
Durak	pility		
5.4	Durability	Class 7: 200,000 cycles	EN 1935:2002/AC:2003
5.8 featur	Families of hinges with common design es	NPD (OBX-20-25.01/160, OBN-20-03.01/160) Same pivot bearing, same roll diameter, same material thickness	
5.5	Corrosion resistance	Class 4: very high corrosion resistance (240 h)	
Dange	erous substances		
ZA.3	Dangerous substances	The materials used in this product do not contain or release any dangerous substances.	

_				
0	Suitable technical	ongoifigation	and/artachnical	dooumontation
$\sim$	Sunable lectioncal	SOECHICAHOL	and/or reconnical	oocumentanon

#### N/A

The performance of the above products complies with the declared performances. The manufacturer mentioned above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) no. 305/2011.

Tobias Schulte, Managing Director of ECO Schulte GmbH & Co. KG	$\Omega - \Omega \Lambda$
(Name of the signatory and function in the company)	J. Schults
Menden, 18.09.2023	
(Place and date of issue)	(Signature)